



WOVEN POLYPROPYLENE TRUCK COVER FABRIC SPECIFICATIONS

| Style # | 10434 | 10434-TR | 10446-TC |
|---|--------------------------------|--------------------------------|--------------------------------|
| FIBER CONTENT | Polypropylene | Polypropylene | Polypropylene |
| FINISH | N/A | Calendered | Calendered |
| COLOR | Black | Black | Black |
| CONSTRUCTION | 53 x 48 | 55 x 48 | 30 x 20 |
| WEIGHT (ASTM D-3776) | 7.8 oz/yd ² | 7.8 oz/yd ² | 6.4 oz/yd ² |
| THICKNESS | 31 MIL | 20 MIL | 14 MIL |
| TENSILE STRENGTH (ASTM D-4632, Grab Method) | Warp: 465 lbs Fill: 400 lbs | Warp: 465 lbs Fill: 400 lbs | Warp: 525 lbs Fill: 290 lbs |
| TEAR STRENGTH (ASTM D-4553, Trap Method) | Warp: 185 lbs Fill: 165 lbs | Warp: 185 lbs Fill: 165 lbs | Warp: 150 lbs Fill: 65 lbs |
| BURST STRENGTH (ASTM D-3786) | 740 lbs/in ² | 700 lbs/in ² | 550 lbs/in ² |

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Product specifications contain typical average values achieved through testing in controlled conditions and are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular use. In no event will Acadian Inc.'s liability exceed the purchase value of the product nor will Acadian Inc. be liable for loss of profit or special, indirect or consequential damages.

UV Inhibitors: Carbon Black
TECHNICAL DATA PROVIDED BY PRODUCING MILL